

# **Technical Data Sheet**

04. Sep. 2015 / Rev No. (1)

#### 1. Product and Introduction

**L322T** 

Product Name	L322T					
Backing Material	Polyester Film					
Bonding	Resin over Resin					
Mineral Type	Aluminum Oxide					
Coating State	Semi-Open coat					
Manufacturing Width	1340mm					

## 2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
						$\triangle$	$\triangle$	•	•	•	•	$\triangle$
	240	280	320	360	400	500	600	800	1000	1200	1500	2000
	•	Δ			•	$\triangle$	•	$\triangle$				

<sup>■</sup> Rough(Grinding)

Finishing (Polishing) ▶

#### 3. Advantage

- ♦ High cutting performance without clogging.
- Good sharpness.
- ♦ Long life time.

### 4. Operation / Application

- ♦ Discs, Sheet.
- ◆ Wood working, Casting, Plastic, etc.

## 5. Work pieces

- ◆ Common painted surface.
- ◆ Wood (solid & Painted ).
- ◆ Plastic (solid & Painted ).

## 6. Available Sander / Grinder

♦ Vibrator.

♦ Orbital sander.

♦ Manual sanding.

<sup>-</sup> Introductory Remarks ●: Standard Grit △: Non Standard Grit