

Technical Data Sheet

Page No. 1

1. Product and Introduction

Product Name	B322T
Backing Material	Latex treated C wt. PAPER
Bonding	Resin over Resin
Mineral Type	Premium Aluminum Oxide (heat treated, tough)
Coating State	Semi - Open coat + Stearate coat
Manufacturing Width	1400mm

2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
						\triangle	•	•	•	•	•	•
	240	280	320	360	400	500	600	800	1000	1200	1500	2000
	•	Δ	•	Δ	•	Δ	•	Δ				

[■] Rough(Grinding)

Finishing(Polishing) ▶

3. Advantage

- ◆ High cutting performance without clogging.
- ♦ Good sharpness.
- ♦ Long life time.

4. Operation / Application

- ♦ Discs, Sheet.
- ◆ Wood working, Casting, Plastic, etc.

5. Work pieces

- ♦ Nonferrous(Al, Zn, etc).
- ◆ Common painted surface.
- ♦ Wood (solid & Painted).

6. Available Sander / Grinder

♦ Vibrator.

◆ Orbital sander.

♦ Manual sanding.

⁻ Introductory Remarks ●: Standard Grit △: Non Standard Grit