

Technical Data Sheet

Page No. 1

1. Product and Introduction

| Product Name | L312T | | | | | |
|---------------------|--|--|--|--|--|--|
| Backing Material | Polyester Film | | | | | |
| Bonding | Resin over Resin | | | | | |
| Mineral Type | Premium Aluminum Oxide (heat treated, tough) | | | | | |
| Coating State | Open coat + Top coat | | | | | |
| Manufacturing Width | 1340mm | | | | | |

2. Available Grit

| Grit | 16 | 24 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 |
|------|-----|-------------|-----|-----|-----|-------------|-----|-----|------|------|------|------|
| | | | | | | | | | | • | • | • |
| | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 |
| | • | \triangle | • | Δ | • | \triangle | • | • | • | • | • | • |

[■] Rough(Grinding)

Finishing(Polishing) ▶

3. Advantage

- ◆ Excellent cutting performance without clogging.
- ◆ Perfect sanding surface.
- ◆ Longer lasting with Durability.
- Especially, excellent for contour sanding without folding.

4. Operation / Application

- ◆ Discs, Long files...
- Automotive refinishing.
- ◆ White wood & Painted surface.

5. Work pieces

- ◆ Automobile.
- ◆ Wood (White & Painted).

6. Available Sander / Grinder

♦ Vibrator.

♦ Orbital sander.

♦ Long file.

⁻ Introductory Remarks ●: Standard Grit △: Non Standard Grit