

# **Technical Data Sheet**

Page No. 1

#### 1. Product and Introduction

Product Name	P355					
Backing Material	Polyester X, Y wt					
Bonding	Resin over Resin					
Mineral Type	Aluminum Oxide					
Coating State	Closed Coat					
Manufacturing Width	1350mm					

### 2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
		•	•	•	•	•	•	•	•	•	•	•
	240	280	320	360	400	500	600	800	1000	1200	1500	2000
	$\triangle$	Δ	•		•							

<sup>■</sup> Rough(Grinding)

Finishing(Polishing) ▶

# 3. Advantage

- ◆ Stiff backing.
- ♦ Fine finishing.
- ◆ Shelling resistance.

## 4. Operation / Application

◆ Wet or Dry Sanding.

◆ P24-60 : Deburring of Al casting.

◆ Fine Grit : Artificial marble, PCB, STS.

## 5. Work pieces

◆ Aluminum.

◆ Stainless steel (Wet).

◆ Carbon steel.

◆ Artificial marble.

◆ P.C.B

#### 6. Available Sander / Grinder

♦ Wide & Narrow Belt Grinder.

628-4, Seonggok-dong, Ansan, Gyeonggi-do, Korea www.sunmight.com

<sup>-</sup> Introductory Remarks ●: Standard Grit △: Non Standard Grit