

Technical Data Sheet

09. Aug. 2016 / Rev No. (0)

1. Product and Introduction

P395A

Product Name	P395A					
Backing Material	100% Polyester Ywt.					
Bonding	Resin over Resin					
Mineral Type	Aluminum Oxide (Compact grain)					
Coating State	Close coat					
Manufacturing Width	1380mm					

2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
						•	•		•	\triangle	•	
	240	280	320	360	400	500	600	800	1000	1200	1500	2000
	•		•		•		•	\triangle				

[◀] Rough(Grinding)

Finishing (Polishing) ▶

3. Advantage

- ◆ Excellent Long life.
- ♦ High productivity.
- ◆ Providing uniform scratch pattern.

4. Operation / Application

- ◆ Stainless steel sheets & coils.
- ♦ Turbine blade.

- ♦ Wet sanding.
- ◆ Welding seams containers.

5. Work pieces

◆ Steel (alloyed, non-alloyed).

◆ Stainless Steel

◆ Non-ferrous metals

6. Available Sander / Grinder

- ◆ Centerless.
- ♦ Wide & Narrow belt.
- ◆ Conveyorized through feed belt grinder.

628-4, Seonggok-dong, Ansan, Gyeonggi-do, Korea www.sunmight.com

⁻ Introductory Remarks ●: Standard Grit △: Non Standard Grit